

Interflon Fin Grease (aerosol) Transparent general purpose grease

Product description

Transparent, multipurpose grease with MicPol® Technology. For a significant reduction of friction, wear and maintenance costs. For use in industry, the food industry and many of other branches. Protects against water and contaminants, steam resistant, transparent and odourless.

Interflon Fin Grease (aerosol) 2 is listed by the NSF for the use in applications with incidental food contact (NSF-H1) with registration number [123184](#) and ISO 21469 certified.

Application

For lubrication of machine parts, like bearings, guides, gears, axles, crown gears, spindles, cables, hinges, shafts, toothed belts, locking pins, valves and many other parts. Especially suited for lubrication at high loads.

Advantages

- Transparent grease, does not stain
- Provides durable lubrication
- Expels water and dirt
- Good penetration properties
- Resistant against steam and water
- Reduces costs because of lower lubrication intervals and wear protection of machine parts

Instructions for use

Shake well before use. Parts should be cleaned first with a solvent or alkaline cleaning agent. Apply thinly.

Safety regulations

See safety data sheet.

Packaging

See our current article list.

Transport regulations

See safety data sheet.

Interflon Fin Grease (aerosol)

Transparent general purpose grease

Technical data

Property	Result	Method
Composition	Mixture of mineral oils, anorganic thickener, solvent, additives and MicPol®. Propellant propane, butane and isobutane.	
Colour	White	
Odour	Recognisable	
Density @ 20°C	0.95 g/cm ³	
NLGI grade	2	ASTM D217
Penetration worked 60 strokes	265	ASTM D217
Penetration worked 100.000 strokes	290	ASTM D217
Roll stability	+ 15 mm	DIN 51804
Dropping point	None	DIN 51801
Base oil viscosity @ 40°C	400 cSt	ASTM D445
SKF Emcor distilled water	1-2	DIN 51802
Copper corrosion	1b	ASTM D4048
Water washout	1.5%	ASTM D1264
Water resistance	1-90	DIN 51807
Dn-factor	250.000	
Lowest application temperature	-20°C	
Highest application temperature*	150°C	
Grease code	KPF2N-20	DIN 51825
Manufacturing date	The batch number consists of a 6-digit number. The last 4 numbers represent the MM/YY of the manufacturing.	
Shelf life**	6 years	

* High temperature limit is valid after evaporation of solvent.

** Shelf life of the product when stored at room temperature in the original and unopened packaging.

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.

INTERFLON BV, P.O. Box 1070
NL-4700 BB Roosendaal, The Netherlands
Tel. + 31 (0) 165 55 39 11 / www.interflon.com

Interflon Fin Grease (aerosol) Transparent general purpose grease

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

Interflon®/MicPol® is a registered trademark of Interflon BV.